

XL50-5000kg

The Multi-Mover XL50 is an electric tow tug which moves everything on wheels up to 5000kg with 2800 Newton tractive force. The XL series has several types of steering, a variety of hitches to choose from, different tyres and is available in 3 very strong and reliable engines.



Specifications :

- 1500 W maintenance-free DC engine, 200A
- 24 Volt DC
- Motor brake and an Electric magnetic brake
- Differential drive
- Axle reinforcement
- 12V 60 AH (2 batteries) Maintenance-free AGM
- 24V 8A High frequency charger, external
- Pull- and push capacity 5000 kg, 2800 Newton.
- Pneumatic tyres 15 inch x 6.00-6, 15cm width, turf profile, 6 inch Rim
- Solid swivel wheel castor, Ø 200mm.
- Ergonomic tiller head
- Potentiometer, continuous
- Battery Discharge indicator
- Battery saving program
- Emergency stop on engine casing
- Buzzer
- Lock with 2 keys
- Ball/Pin coupler op 45 cm height
- Ball/Pin coupler on 65 cm height
- Hitchplate with holes with M12 thread on different heights

Dimensions :

- Weight : 200-400kg
- Length : 165cm
- Width : 70/80cm
- Height : 103cm

Tyre Options

Ideal for hard surface like asphalt, concrete, pavement and hard lawn



Pneumatic block tread
15"



Pneumatic block tread
16"



Pneumatic block tread



Pneumatic block tread
16"



Pneumatic block tread
18"

Hard surface like asphalt and concrete.



Solid rubber tyres Conti-
nental K 4.00-8/3.00



Solid rubber tyres Conti-
nental K125/75-8/3.00

Hard surface like asphalt and concrete. (Non Marking)



Solid rubber tyres Conti-
nental K 4.00-8/3.00



Solid rubber tyres Conti-
nental K125/75-8/3.00



Pneumatic block tread
non marking 16"

Snow, Rocky, Sand and Gravel Surface



Pneumatic winter tyres
18"



Pneumatic Tractor tyres
16"



Pneumatic winter tyres
16"



Pneumatic winter tyres
16"

Sand, Fields and Gravel Surface



Pneumatic Tractor tyres
18"



Pneumatic Tractor tyres
16"

Castors



Solid wheel swivel
castor



Solid double wheel
swivel castor



Solid wheel swivel cas-
tor non marking



Solid double wheel swivel
castor non marking



Pneumatic wheel swivel
castor



Pneumatic wheel swivel
castor



Pneumatic Double
wheel swivel castor



Solid Double Wheel
Steering Castor



Double Single Castor
Wheels

Wheel Options



Galvanised Anti
Wheely Wheels



Galvanised Anti
Wheely Wheels



Painted Anti
Wheely Wheels


Hitch + Light Options

Hitches



Bolt Hitches

For all Multi-Mover models.
Different sizes, bolts and space.



Bolt Hitch / Towbar

Available on Multi-Mover M18, M18SV, L25, XL and XXL
Default ball model, to be fixed e.g. on a 45 cm height.
The height of a car's towing hook.



Drawbars

For all Multi-Mover Models
Different Models Available
Various sizes 3,500kg and 20,000kg



Rockinger Tow Hitch RO 244 A

Available on Multi-Mover M18, M18SV, L25, XL, and XXL
Automatic trailer coupling RO244A
Up to 20T
Optional with Bowden Cable, remote control.
Can be mounted on Hydraulic options A,B and C



Rockinger Tow Hitch RO244 L

Available on Multi-Mover M18, M18SV, L25, XL, and XXL
Pedal Operated

Can be mounted on Hydraulic options A,B and C



NATO Towing and Hook Trailer Hitches

Available on all models
Hook trailer hitch with safety lock
Nato Hitch

Hydraulic Lifting



Automatic Coupling A

Hydraulic Lift A with 2 coupling points. Lifts from 25 cm to 45 cm and from 45 cm to 65 cm height.
Maximum lifting 300 – 400 Kg
Available Also on XL35 and XL75



Automatic Coupling B

Hydraulic lift with coupling from 0 cm to 70 cm, 110 cm or 130 cm height.
Maximum lifting 200– 600 Kg
Available Also on XL, XXL, 3XL and 4XL



Automatic Coupling C

XL50– 52cm to 72cm Height Max 300kg
Available Also on XL, XXL, 3XL and 4XL

Lights / Sounders



Warning System LED Flashlight

Optical on 160 cm high pole



Warning System LED Flashlight

Optical back side tiller arm SDK



Working headlight LED mounted



Audible Warning

We offer multiple audible warnings from alarms while in motion to buzzers and horns.